



## BUILDING PRODUCTS LISTING PROGRAM

Customer: Oks Poly Co., Ltd  
Class: Housewrap  
Location: Daegu, South Korea  
Website: [www.okspoly.com](http://www.okspoly.com)

Listing No. B1144-1

Effective Date: December 30, 2023  
Last Revised Date: December 30, 2023  
Expires: <N/A>

Standards:	ASTM E2556	<i>Standard Specification for Vapor Permeable Flexible Sheet Water-Resistive Barriers Intended for Mechanical Attachment</i>
	ASTM E2178	<i>Standard Test Method for Air Permeance of Building Materials</i>
	ASTM E2273	<i>Standard Test Method for Determining Efficiency of Exterior Insulation and Finish Systems (EIFS) Clad Wall Assemblies</i>
	ASTM E2357	<i>Standard Test Method for Determining Air Leakage of Air Barrier Assemblies</i>
	ASTM E84	<i>Standard Method of Test for Surface Burning Characteristics of Building Materials</i>

Product:	Model	Width	Length	Weight
	XTRIMWRAP 90 Housewrap	Manufactured in rolls of varying sizes: 3-ft, 9-ft, 10-ft	Manufactured in rolls of varying sizes according to the customer's request	90 g/m <sup>2</sup>

Markings: Listed products are identified with a label bearing the following information:

- Product Identification
- Company name, logo, address
- Product name
- QAI file number: B1144-1
- Information for traceability
- Roll length and width
- QAI logo shown here:





Ratings:

Product	Test Method	Classification/Rating
XTRIMWRAP 90	ASTM E2556	Type II
	ASTM E2178	Air Permeance < 0.02 L/(s*m <sup>2</sup> )
	ASTM E2273	Drainage Efficiency > 75%
	ASTM E2357	Air Leakage of Wall Assembly < 0.04 cfm/ft <sup>2</sup>
	ASTM E84	Class A

<b>XTRIMWRAP 90 Air Barrier Wall Assembly</b>	
Framing	2-inch x 4-inch nominal framing members installed at 16-inch on center.
Sheathing	15/32-inch OSB Exposure 1 rated sheathing attached to the framing with fasteners at 6-inch on center around the perimeter and 12-inch on center in the field.
Air Barrier	XTRIMWRAP 90 housewrap installed over the exterior surface of the OSB sheathing following the manufactures installation instructions. Horizontal lap seams shall have a minimum 6-inch overlap and vertical laps shall have a minimum 6-inch overlap. All joints shall be sealed with 3-inch width Fortifber® Sheathing Tape. Nominal 1-inch x 2-inch wooden battens shall be placed along each stud and fastened to the framing at 16-inches on center.  Any penetrations shall be sealed following the manufacturer’s installation instructions and using a 3-inch wide Fortifber® Sheathing Tape.

Notes: This product must be installed in accordance with the code enforced by the authority having jurisdiction. Final acceptance of the product in the final installation is subject to inspection by the authority having jurisdiction.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at [www.qai.org](http://www.qai.org) for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to [info@qai.org](mailto:info@qai.org). Please include the listing number in the request.

\*\*\*