



WINDOWS & DOORS LISTING PROGRAM

Customer: Centra Windows Inc.
Class: Fenestration Products – Energy Performance
Location: Calgary, Alberta
Website: www.centra.ca

Listing No. W462-6
Project No. W462-6 ED2
Effective Date: April 22, 2024
Last Revised Date: June 3, 2024
Expires: N/A

Standards: CSA A440.2 “Fenestration Energy Performance”

Product: Vinyl Doors

Markings: Products are marked with the following content in a permanent manner where it is readily visible after installation:

- a) Manufacturer’s name, Trademark or other recognized symbol or identification.
- b) QAI file Number: W462
- c) QAI logo shown here:



- d) “Evaluation for energy performance in accordance with CSA A440.2” / “Évalué pour la performance d’énergie en accord à la norme CSA A440.2”

Models / Ratings:

5200 Series Sliding Door

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	CW-5200SD-3,180(2)-3,180(4)-3,i89(6)-8AR90EN-R1	1.12	0.43	40
G02	CW-5200SD-3,180(2)-3,270(4)-3,i89(6)-8AR90EN-R1	1.11	0.31	33
G03	CW-5200SD-3,270(2)-3,180(4)-3,i89(6)-8AR90EN-R1	1.11	0.26	31
G04	CW-5200SD-3,270(2)-3,270(4)-3,i89(6)-8AR90EN-R1	1.10	0.23	29
G05	CW-5200SD-3,270(2)-3,366(4)-3,i89(6)-8AR90EN-R1	1.09	0.20	27



Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G06	CW-5200SD-3,366(2)-3,270(4)-3,i89(6)-8AR90EN-R1	1.09	0.18	26
G07	CW-5200SD-3,366(2)-3,366(4)-3,i89(6)-8AR90EN-R1	1.08	0.17	26
G08	CW-5200SD-3,180(2)-3,CL-3,180(5)-8AR90EN-R1	1.25	0.45	38
G09	CW-5200SD-3,CL-3,180(3)-3,180(5)-8AR90EN-R1	1.25	0.47	40
G10	CW-5200SD-3,CL-3,CL-3,180(5)-8AR90EN-R1	1.47	0.49	36
G11	CW-5200SD-3,270(2)-3,CL-3,270(5)-8AR90EN-R1	1.21	0.26	28
G12	CW-5200SD-3,366(2)-3,CL-3,270(5)-8AR90EN-R1	1.20	0.20	25
G13	CW-5200SD-3,270(2)-3,CL-3,180(5)-8AR90EN-R1	1.23	0.27	28

Notes:

- Products are not intended for installation in storefronts, non-operable portions of curtain wall, fixed glazing cast into precast concrete panels, greenhouses, skylights or sloped glazing.
- Test procedures are designed to test the performance of the test specimen only and are not necessarily used to test the performance of the installation, particularly the perimeter sealant joint and anchoring of the assembly.
- The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI.
- No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing.
- Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.