

## FIRE DOOR LISTING PROGRAM

Customer: HOME FACTORIES, INC. DBA BMD MANUFACTURING  
 Class: Fire Doors  
 Location: Galt, CA  
 Website: <https://bmdmfg.com/>

Listing No. F496  
 Project No. F496-1 Edition 1

Effective Date: August 19, 2024  
 Last Revised Date: August 19, 2024

Standards: CAN/ULC S104 UL 10B UL 10C NFPA 252	<i>Standard Method for Fire Tests of Door Assemblies. Fire Tests of Doors Assemblies. Fire Tests of Doors Assemblies. Standard Methods of Fire Tests of Door Assemblies.</i>
---	--

Product: 20-Minute Fire-Resistance Rated Doors

Markings: See [FD001 - Fire Door Labeling requirements](#)

Models: **GLENVIEW 20-MINUTE FIRE-RESISTANCE RATED CATEGORY “B” DOORS:**

**Minimum 44 mm (1-3/4”) Thickness**

Swing Type:	Maximum Dimensions		Panel Type:	Latching:
	Width:	Length:		
<b>Single Swing</b>	42 in. (1067 mm)	96 in. (2438 mm)	Flush	Single Point Mortised or cylindrical

**COMPONENTS LIMITATIONS:** (Review Machining Report for further detail)

**Latch Sets**

- Listed mortise or cylindrical lockset hardware approved for use with 20-minute wood type doors.

**Hinges** (Listed and labeled for rated opening)

- Hinges as per NFPA 80, Table 6.4.3.1.
- Pol-Soft Estetic 150
- Simonswerk Tectus 340 3D

**Fire Exit Devices** (Listed and labeled for rated opening)

- Surface mounted hardware permitted.

**Door Closers**

- Mortised closers of maximum size 19-11/16” x 2-5/16” x 1-3/8”.
- Surface mounted door closers.

**Louvers**

- Not Permitted

**Viewers** (Listed and labeled for rated opening)

- Not Permitted

**Glass Lights**

- Not Permitted

**Door Bottoms Seals**

- Mortised door bottom seals.
- Plant on door bottom seals.

**Electric Raceway**

- Not Permitted

Notes: *Refer to QAI evaluation report F411-1 and the applicable test reports for test assembly configurations used for fire endurance testing.*

*Refer to the [QAI FD002 - Fire Door Guidelines for general guidelines of fire door assemblies](#)*

*Final acceptance of the product in the intended application is to be determined by the authority having jurisdiction (AHJ).*

*Product is to be installed in accordance with the manufacturer's published installation instructions by qualified installing personnel.*

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at [www.qai.org](http://www.qai.org) for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to [info@qai.org](mailto:info@qai.org). Please include the listing number in the request.

\*\*\*