

## **ELECTRICAL LISTING PROGRAM**

Customer: Dream Lighting INC.  
Class: RV Luminaires  
Location: Elkhart, IN, USA

Listing No. E10593  
Report No. E10593-1602 Edition 8  
Project No. E10593-2401  
Effective Date: Sep 10, 2024  
Last Revised N/A  
Date:  
Expires: N/A

Standards: CSA C22.2 No. 250 – Luminaires  
CSA C22.2 No. 250.13 - Light emitting diode (LED) equipment for lighting applications  
UL 234 - Low Voltage Lighting Fixtures for Use in Recreational Vehicles  
UL 8750 - Light Emitting Diode (LED) Equipment for Use in Lighting Products

Product: Recreational Vehicles Luminaires, Indoor & Outdoor use, permanently connected.

Markings: Products are marked in a permanent manner where it is readily visible after installation with the following:

- a) Manufacturer's name or trademark
- b) Model designation
- c) Month and year of manufacture
- d) Product ratings: voltage, frequency, watts
- e) QAI file Number: E10593
- f) The wording "CSA C22.2 No. 250.0 and UL 234"
- g) Warning markings as required by the standards in English and French
- h) QAI logo shown here:



## Models / Ratings:

| Model #                     | Description  | Volts (Vdc) | Wattage (W) | Location |
|-----------------------------|--|-------------|-------------|----------|
| 0016264 <sup>*1,8</sup>     | 4.5" LED Mushroom Light                            | 12          | 5.3         | Damp     |
| 0016263 <sup>*1,8</sup>     | 3.5" LED Mushroom Light                            | 12          | 3           | Damp     |
| 0016274 <sup>*1,4,8</sup>   | 4.5" LED Mushroom Light with Switch                | 12          | 5.3         | Damp     |
| 0016282 <sup>*1,8</sup>     | 3" Recessed Light                                  | 12          | 3           | Dry      |
| 0016285 <sup>*1,8</sup>     | 4" Recessed Light                                  | 12          | 3.6         | Dry      |
| 0016043 <sup>*1,5,6,9</sup> | LED Single Pancake Light                           | 12          | 4.5         | Damp     |
| 0016045 <sup>*1,5,6,9</sup> | LED Double Pancake Light                           | 12          | 7.5         | Damp     |
| 0016048 <sup>*1,6,9</sup>   | LED Sensor Light                                   | 12          | 6           | Damp     |
| 0013612 <sup>*2,6,9</sup>   | Dual Color Awning Light (Polymeric) without Switch | 12          | 4.5         | Wet      |
| 0013612                     | Dual Color Awning Light (Polymeric) with Switch    | 12          | 4.5         | Damp     |
| 0013712 <sup>*1,6,7</sup>   | Single Color Awning Light (Metal)                  | 12          | 6.5         | Wet      |
| 0043616 <sup>*3</sup>       | Strip Light (up to 5 meters)                       | 12          | 6.72        | Damp     |
| 0016294-XXX                 | Recessed Ceiling Light                             | 12          | 5           | Damp     |
| EA-XCW-B-XX                 | Awning Light                                       | 12          | 5           | Wet      |
| DWS-X4XX                    | Wall Light   | 12          | 4           | Dry      |
| DWSV-X4XX                   | Color Changeable Wall Light                        | 12          | 4           | Dry      |
| DP-M6XX                     | Pendant Light                                      | 12          | 6           | Dry      |
| DD-X6XX                     | Dinette Light                                      | 12          | 6           | Dry      |
| ICD-XXX                     | Recessed Ceiling Light                             | 12          | 4           | Damp     |
| ICB-X5-HMXX                 | Hand Motion Light                                  | 12          | 5           | Damp     |
| DP-G4XX                     | Glass Pendant Light                                | 12          | 4           | Dry      |
| DV-X4XX                     | Cosmetic Light                                     | 12          | 7           | Damp     |
| 0011203-XX                  | Inside Step Light                                  | 12          | 1.2         | Dry      |
| CLSI-70-XXX                 | Cabinet Door Light                                 | 12          | 0.9         | Dry      |
| EU2CW-S-XXX                 | Front Hatch Area Light                             | 12          | 4.7         | Damp     |
| 0016273-XX                  | Inside Light                                       | 12          | 3.8         | Damp     |
| USB-W-XXX                   | Reading Light with USB                             | 12          | 2           | Dry      |
| USB-V-XXX                   | Wall Light with USB                                | 12          | 6.5         | Dry      |
| 0016292-XXX                 | Ceiling Mounted Luminaire                          | 12          | 3.5         | Dry      |
| 0016924-XXX                 | Ceiling Mounted Luminaire                          | 12          | 9           | Dry      |
| 0016296-XXX <sup>*10</sup>  | Ceiling Mounted Luminaire                          | 12          | 6           | Dry      |
| 0016299-XXX <sup>*10</sup>  | Ceiling Mounted Luminaire                          | 12          | 6.5         | Dry      |
| 0043615COB-XXX              | Strip Light (up to 5 meters)                       | 12          | 27          | Damp     |

## NOTES\*:

1. Will be available in warm white and cool white color LEDs.
2. Will be available in warm white, cool white and amber color LEDs.
3. Will be available in warm white, cool white, amber, blue, green, red color LEDs.

4. Will be available with glowing or without glowing within the switch.
5. Will be available with or without switch.
6. Will be available in black and white enclosure.
7. Will be available in clear lens.
8. Will be available in frosted lens.
9. Will be available in clear and frosted lens.
- 10: USB rating: 5Vdc, 2.1A max.

Where: XXX = Maybe set of number used by the manufacture to signify non-critical, indication LED temp, customer ID, enclosure color, pattern or other cosmetic feature not affecting safety or product function. For the strip light, the maximum length is limited within 196 inches by manufacture. It can be cut in any size to be used without safety issue.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at [www.qai.org](http://www.qai.org) for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to [info@qai.org](mailto:info@qai.org). Please include the listing number in the request.

\*\*\*