

## BUILDING PRODUCTS LISTING PROGRAM

Customer: **DAP Global Inc.**

Class: Thermal Insulation

Location: Fenton, MO

Website: [www.dap.com](http://www.dap.com)

Listing No. B1162

Project No. B1162 - Edition 2

Effective Date: April 11, 2025

Last Revised Date: November 17, 2025

Standards: ASTM E84-21 "Standard Test Method for Surface Burning Characteristics of Building Materials"

Product: DAP Polyurethane Foam Plastic Insulation

**I. Touch N' Seal® Class I FR Spray Foam System**

- Pro System 110 (Low GWP)
- Pro System 200 (Low GWP)
- Pro System 600 (Low GWP)
- Constant Pressure Foam Pro System CP-750FR (Low GWP)
- Refill System RF-17FR (Low GWP)
- Refill System RF-60FR (Low GWP)

**II. Touch N' Foam® Professional Class I FR Spray Foam System**

- Pro System 110 (Low GWP)
- Pro System 200 (Low GWP)
- Pro System 600 (Low GWP)
- Constant Pressure Foam Pro System CP-750FR (Low GWP)

**III. Touch N' Seal® HVAC 1.75 Spray Foam System**

- HVAC 1.75 Pro System 110 (Low GWP)
- HVAC 1.75 Pro System 200 (Low GWP)
- HVAC 1.75 Pro System 600 (Low GWP)
- HVAC 1.75 Constant Pressure Foam System HVAC-750 (Low GWP)
- Refill System RF-17FR HVAC (Low GWP)
- Refill System RF-60FR HVAC (Low GWP)

Markings: Finished packaging of the A and B components for each product made using Formula F3953 must be marked in a permanent manner with the following information:

- a) Manufacturer's Name or Trademark
- b) Product Model
- c) Traceability code
- d) ASTM E84 Flame Spread and Smoke Developed Rating -  
FSI ≤ 25, SDI ≤ 450
- e) QAI File Number (B1162)
- f) QAI logo as shown here:



Models: The following outlines the performance of the DAP products determined in accordance with the noted standards:

DAP Polyurethane Foam Plastic Products Surface Burning Characteristics per ASTM E84-21:

Foam System(s)	Low GWP Model(s)	Flame Spread Index	Smoke Developed Index	Maximum Thickness (inches)
Touch N' Seal® Class I FR Spray Foam System	Pro System 110	≤ 25	≤ 450	2
	Pro System 200			
	Pro System 600			
	Constant Pressure Foam Pro System CP-750FR			
	Refill System RF-17FR			
	Refill System RF-60FR			
Touch N' Foam® Professional Class I FR Spray Foam System	Pro System 110	≤ 25	≤ 450	2
	Pro System 200			
	Pro System 600			
	Constant Pressure Foam Pro System CP-750FR			
Touch N' Seal® HVAC 1.75 Spray Foam System	HVAC 1.75 Pro System 110	≤ 25	≤ 450	2
	HVAC 1.75 Pro System 200			
	HVAC 1.75 Pro System 600			
	HVAC 1.75 Constant Pressure Foam System HVAC-750			
	Refill System RF-17FR HVAC			
	Refill System RF-60FR HVAC			

Notes: Products are subjected to limitations as specified above and must be installed in accordance with the manufacturer's instructions. Authorities having jurisdiction should be consulted regarding allowable applications.

Listed manufacturers are subject to on-going inspections by QAI to ensure that the products outlined above remain as it is listed.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at [www.qai.org](http://www.qai.org) for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to [info@qai.org](mailto:info@qai.org). Please include the listing number in the request.

\*\*\*