



BUILDING PRODUCT LISTING PROGRAM

Customer: OnDek Vinyl Worx, Inc.
Class: Polyvinyl-Chloride Roofing and Walking Decks
Location: Langley, BC Canada
Website: <https://ondekvinylworx.com>

Listing No. B1166
Project No. B1166, Edition 1

Effective Date: June 27, 2025
Last Revised: June 27, 2025
Expires: N/A

Standards: ASTM E108-20 "Standard Test Methods for Fire Tests of Roof Covering"
CAN/ULC S107-19 "Standard Methods of Fire Tests of Roof Coverings"
CAN/CGSB 37.54-95 "Polyvinyl Chloride Roofing and Waterproofing Membrane"

Product: OnDek 60 mil externally reinforced nonwoven PVC

Markings: Each roll of OnDek 60 mil external reinforced product is marked with a permanent label containing the following information:

- a) OnDek name or trademark
- b) Product name or product number
- c) Month and year of manufacture
- d) QAI logo with 'c' and 'us' indicators
- e) CGSB Type 3 Class B
- f) QAI file Number: B1166
- g) QAI logo shown here:



Models / Ratings:

Model	Nominal thickness	Surface	Roll Width(s)
OnDek 60 mil externally reinforced	60 mils (1.5 mm)	Embossed	72-inches



Results:

Standard	Details	Rating
CAN/CGSB 37.54	OnDek 60 mils externally reinforced	Type 3, Class B

ASTM E108 / CAN/ULC S107: Decking Assembly Details

Rating:	Class A
Deck Slope Maximum:	1/4 : 12
Deck Sheathing:	Non-combustible sheathing defined and installed in accordance with the applicable code.
Approved Membrane(s):	OnDek 60 mil externally reinforced (1.5 mm) adhered to the non-combustible substrate with 0280 all season contact adhesive (solvent-based) applied per OnDek installation instructions at a rate of 1.47 m ² /L (60 ft ² /gallon) coverage.

Rating:	Class C
Deck Slope Maximum:	1/4 : 12
Deck Sheathing:	Minimum 12 mm (15/32") AC Exterior grade plywood. All deck joints are covered evenly with Mapei Planiprep SC Seam patch at a minimum thickness of 3 mm (1/8") prior to the membrane application.
Approved Membrane(s):	OnDek 60 mil externally reinforced (1.5 mm) adhered to the non-combustible substrate with 0280 all season contact adhesive (solvent-based) applied per OnDek installation instructions at a rate of 1.47 m ² /L (60 ft ² /gallon) coverage.

Products must be installed with the manufacturer's published installation instructions and in accordance with the building codes recognized by the authority having jurisdiction.

Listed manufacturers are subject to on-going inspections by QAI to ensure that the products outlined above remains as it is listed.



Notes:

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
