



WINDOWS & DOORS LISTING PROGRAM

Customer: Aegis Building Supplies Ltd.
Class: Fenestration Products – Energy Performance
Location: Richmond, British Columbia
Website: www.aegissupply.ca

Listing No. W608-1
Project No. W608-1 ED1
Effective Date: August 6, 2026
Last Revised Date: August 6, 2026
Expires: N/A

Standards: CSA A440.2-22 “Fenestration Energy Performance”

Product: Vinyl Windows

Markings: Products are marked with the following content in a permanent manner where it is readily visible after installation:

- a) Manufacturer’s name, Trademark or other recognized symbol or identification.
- b) QAI file Number: W608
- c) QAI logo shown here:



- d) “Evaluation for energy performance in accordance with CSA A440.2” / “Évalué pour la performance d’énergie en accord à la norme CSA A440.2”

**Models / Ratings:****80 Series Fixed Window**

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	ABS-80FX-6,X187(2)-6,CL-12AR90T13-R1-G1<1	1.56	0.40	29
G02	ABS-80FX-6,Y146(2)-6,YEA(4)-12AR90T13-R1	1.26	0.21	25
G03	ABS-80FX-6,Y146(2)-6,YEA(4)-12AR90T13-R1	1.26	0.21	25
G04	ABS-80FX-6,LB60(2)-6,CL-12AR90T13-R1	1.46	0.24	22
G05	ABS-80FX-6,LB60(2)-6,CL-12AR90T14-R1	1.46	0.24	22
G06	ABS-80FX-8,Y670(2)-8,CL-16AR90T13-R1	1.47	0.23	21
G07	ABS-80FX-8,Y156T(2)-8,CL-16AR90T13-R1	1.48	0.19	19
G08	ABS-80FX-10,Y152(2)-10,CL-16AR90T13-R1	1.48	0.20	19
G09	ABS-80FX-5,S116(2)-5,CL-5,S116(5)-12AR90T14-R1	0.94	0.38	41
G10	ABS-80FX-5,S116(2)-5,CL-5,S116(5)-12AR90T14-R1	1.01	0.38	40
G11	ABS-80FX-6,XD221(2)-6,X179(4)-5,CL-12AR90T13-R1	0.92	0.20	31
G12	ABS-80FX-6,XD221(2)-6,X179(4)-5,CL-12A100T13-R1	1.08	0.20	28
G13	ABS-80FX-6,XD221(2)-6,X179(4)-6,CL-12AR90AL-R1	0.99	0.20	30
G14	ABS-80FX-6,X150(2)-6,X150(4)-6,CL-12AR90T13-R1-G1<1	0.94	0.12	26
G15	ABS-80FX-6,X150(2)-6,X150(4)-6,CL-12AR90T13-R1	0.94	0.13	27
G16	ABS-80FX-6,X187(2)-6,CL-6,CL-12AR90T13-R1	1.22	0.40	36
G17	ABS-80FX-6,Y146(2)-6,YEA6(4)-6,CL-12AR90T13-R1	0.98	0.19	30
G18	ABS-80FX-6,Y152(2)-6,YEA(4)-6,CL-12AR90T13-R1	0.97	0.18	29
G19	ABS-80FX-6,Y175(2)-6,Y175(4)-6,CL-12AR90T13-R1	0.92	0.24	34
G20	ABS-80FX-6,Y175(2)-6,Y175(4)-6,CL-12AR90T13-R1	0.92	0.24	34
G21	ABS-80FX-6,S52N(2)-6,CL-6,CL-12AR90T13-R1	1.16	0.18	25
G22	ABS-80FX-6,Y175(2)-6,Y175(4)-6,CL-12AR90AL-R1	0.99	0.24	32
G23	ABS-80FX-6,Y152(2)-6,YEA6(4)-6,CL-12AR90AL-R1	1.04	0.18	28
G24	ABS-80FX-6,S52N(2)-6,S52N(4)-6,CL-12AR90T14-R1	0.90	0.14	28
G25	ABS-80FX-5,N180(2)-5,CL-5,N180(5)-12AR90T13-R1	1.00	0.37	39
G26	ABS-80FX-5,N180(2)-5,CL-5,CL-12AR90T13-R1	1.24	0.40	36

80 Series Awning Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	ABS-80AW-6,X187(2)-6,CL-12AR90T13-R1-G1<1	1.57	0.24	19
G02	ABS-80AW-6,Y146(2)-6,YEA(4)-12AR90T13-R1	1.40	0.13	17
G03	ABS-80AW-6,Y146(2)-6,YEA(4)-12AR90T13-R1	1.40	0.13	17
G04	ABS-80AW-6,LB60(2)-6,CL-12AR90T13-R1	1.51	0.15	15
G05	ABS-80AW-6,LB60(2)-6,CL-12AR90T14-R1	1.51	0.15	15
G06	ABS-80AW-8,Y670(2)-8,CL-16AR90T13-R1	1.48	0.15	16
G07	ABS-80AW-8,Y156T(2)-8,CL-16AR90T13-R1	1.49	0.12	14
G08	ABS-80AW-10,Y152(2)-10,CL-16AR90T13-R1	1.49	0.13	15
G09	ABS-80AW-5,S116(2)-5,CL-5,S116(5)-12AR90T14-R1	1.12	0.23	29
G10	ABS-80AW-5,S116(2)-5,CL-5,S116(5)-12AR90AL-R1	1.22	0.23	26
G11	ABS-80AW-6,XD221(2)-6,X179(4)-5,CL-12AR90T13-R1	1.13	0.13	23
G12	ABS-80AW-6,XD221(2)-6,X179(4)-5,CL-12A100T13-R1	1.23	0.13	20



Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G13	ABS-80AW-6, XD221(2)-6, X179(4)-6, CL-12AR90AL-R1	1.21	0.13	21
G14	ABS-80AW-6, X150(2)-6, X150(4)-6, CL-12AR90T13-R1-G1<1	1.13	0.08	20
G15	ABS-80AW-6, X150(2)-6, X150(4)-6, CL-12AR90T13-R1	1.13	0.08	20
G16	ABS-80AW-6, X187(2)-6, CL-6, CL-12AR90T13-R1	1.29	0.25	26
G17	ABS-80AW-6, Y146(2)-6, YEA6(4)-6, CL-12AR90T13-R1	1.16	0.12	21
G18	ABS-80AW-6, Y152(2)-6, YEA6(4)-6, CL-12AR90T13-R1	1.14	0.11	21
G19	ABS-80AW-6, Y175(2)-6, Y175(4)-6, CL-12AR90T13-R1	1.12	0.15	24
G20	ABS-80AW-6, Y175(2)-6, Y175(4)-6, CL-12AR90T13-R1	1.12	0.15	24
G21	ABS-80AW-6, S52N(2)-6, CL-6, CL-12AR90T13-R1	1.26	0.11	19
G22	ABS-80AW-6, Y175(2)-6, Y175(4)-6, CL-12AR90AL-R1	1.21	0.15	22
G23	ABS-80AW-6, Y152(2)-6, YEA6(4)-6, CL-12AR90AL-R1	1.24	0.11	19
G24	ABS-80AW-6, S52N(2)-6, S52N(4)-6, CL-12AR90T14-R1	1.11	0.09	21
G25	ABS-80AW-8, X180(2)-8, CL-16AR90T13-R1	1.50	0.20	19
G26	ABS-80AW-5, S116(2)-5, CL-5, CL-12AR90T13-R1	1.28	0.25	26

80 Series Casement Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	ABS-80CA-6, X187(2)-6, CL-12AR90T13-R1-G1<1	1.57	0.24	19
G02	ABS-80CA-6, Y146(2)-6, YEA(4)-12AR90T13-R1	1.39	0.13	17
G03	ABS-80CA-6, Y146(2)-6, YEA(4)-12AR90T13-R1	1.39	0.13	17
G04	ABS-80CA-6, LB60(2)-6, CL-12AR90T13-R1	1.51	0.15	15
G05	ABS-80CA-6, LB60(2)-6, CL-12AR90T14-R1	1.51	0.15	15
G06	ABS-80CA-8, Y670(2)-8, CL-16AR90T13-R1	1.47	0.15	16
G07	ABS-80CA-8, Y156T(2)-8, CL-16AR90T13-R1	1.47	0.12	15
G08	ABS-80CA-10, Y152(2)-10, CL-16AR90T13-R1	1.48	0.13	15
G09	ABS-80CA-5, S116(2)-5, CL-5, S116(5)-12AR90T14-R1	1.11	0.23	29
G10	ABS-80CA-5, S116(2)-5, CL-5, S116(5)-12AR90T14-R1	1.22	0.23	26
G11	ABS-80CA-6, XD221(2)-6, X179(4)-6, CL-12AR90T13-R1	1.14	0.13	22
G12	ABS-80CA-6, XD221(2)-6, X179(4)-5, CL-12A100T13-R1	1.23	0.13	20
G13	ABS-80CA-6, XD221(2)-6, X179(4)-6, CL-12AR90AL-R1	1.21	0.13	21
G14	ABS-80CA-6, X150(2)-6, X150(4)-6, CL-12AR90T13-R1-G1<1	1.13	0.08	20
G15	ABS-80CA-6, X150(2)-6, X150(4)-6, CL-12AR90T13-R1	1.13	0.08	20
G16	ABS-80CA-6, X187(2)-6, CL-6, CL-12AR90T13-R1	1.29	0.25	26
G17	ABS-80CA-6, Y146(2)-6, YEA6(4)-6, CL-12AR90T13-R1	1.15	0.12	22
G18	ABS-80CA-6, Y152(2)-6, YEA6(4)-6, CL-12AR90T13-R1	1.14	0.11	21
G19	ABS-80CA-6, Y175(2)-6, Y175(4)-6, CL-12AR90T13-R1	1.12	0.15	24
G20	ABS-80CA-6, Y175(2)-6, Y175(4)-6, CL-12AR90T13-R1	1.12	0.15	24
G21	ABS-80CA-6, S52N(2)-6, CL-6, CL-12AR90T13-R1	1.26	0.11	19
G22	ABS-80CA-6, Y175(2)-6, Y175(4)-6, CL-12AR90AL-R1	1.21	0.15	22
G23	ABS-80CA-6, Y152(2)-6, YEA6(4)-6, CL-12AR90AL-R1	1.23	0.11	19
G24	ABS-80CA-6, S52N(2)-6, S52N(4)-6, CL-12AR90T14-R1	1.11	0.09	21
G25	ABS-80CA-8, X180(2)-8, CL-16AR90T13-R1	1.50	0.20	19
G26	ABS-80CA-5, S116(2)-5, CL-5, CL-12AR90T13-R1	1.27	0.25	26



Notes:

- Products are not intended for installation in storefronts, non-operable portions of curtain wall, fixed glazing cast into precast concrete panels, greenhouses, skylights or sloped glazing.
- Test procedures are designed to test the performance of the test specimen only and are not necessarily used to test the performance of the installation, particularly the perimeter sealant joint and anchoring of the assembly.
- The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI.
- No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing.
- Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.